

4.8HP 5.2HP 7.8HP Air Cooled Single Cylinder Diesel Engine GET190F

Basic Information

. Place of Origin: China Brand Name: GET ISO CE · Certification: Model Number: GET190F • Price: Negotiable Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-• Payment Terms: amount payment, Money Gram



Product Specification

. Type: Single Cylinder, Vertical, Four-stroke, Direct

Injection, Air-cooled

73x59mm, 78x62mm, 86x72mm Borexstroke:

247ml, 296ml, 418ml Displacement: 20:01, 20:01, 19:01 . Compression Ratio:

3.5/3000-3.8/3600 3.68/3000-Rated Power(kw/rpm): 4/3600 5.7/3000-6.3/3600

Rated Power(hp/rpm): 4.8/3000-5.2/3600, 5.0/3000-5.4/3600,

7.8/3000-8.6/3600

• Rated Speed(rpm): 3000/3600 • Lowest Rotation Speed At ≤1300r/min

Zero Load:

Lubricating System: Pressure Splashed Recoil Start/electric Starter . Starting System:

• Rotation Direction(face To Anticlockwise

The Output Axle):

O#/arramar\ 10#/winter\ OE#/abillages\

Product Description

GET190F Single Cylinder Air Cooled Diesel Engine Air Cooled Generator

A single-cylinder air-cooled diesel engine typically possesses the following features:

Cylinder Configuration: It has a single cylinder where the combustion process takes place. This design simplifies the engine's construction and reduces complexity.

Air Cooling System: Instead of using a liquid cooling system, the engine is cooled by air. It incorporates cooling fins on the cylinder and sometimes on the cylinder head to dissipate heat generated during operation. The air-cooling system eliminates the need for a radiator, coolant, and associated maintenance.

Fuel Type: It operates on diesel fuel, which is ignited through compression rather than a spark plug, as in gasoline engines. Diesel fuel offers better energy efficiency and higher torque compared to gasoline.

Power Output: Single-cylinder air-cooled diesel engines are typically used in smaller applications and may have lower power outputs compared to multi-cylinder engines. The power output can vary based on the engine size, design, and intended use. Efficiency and Durability: Diesel engines are known for their efficiency and durability. Single-cylinder air-cooled diesel engines offer good fuel efficiency and can withstand continuous operation in various conditions.

Compression Ratio: Diesel engines have higher compression ratios compared to gasoline engines. The high compression ratio allows for efficient combustion of diesel fuel, resulting in improved fuel efficiency and torque output.

Lubrication System: The engine includes an oil lubrication system to ensure proper lubrication of moving parts and reduce friction. Regular maintenance, such as oil changes, is necessary to maintain optimal performance.

Applications: Single-cylinder air-cooled diesel engines are commonly used in small machinery, generators, water pumps, agricultural equipment, and other portable or compact applications where a simple and reliable power source is required.

Model	GET188F	GET190F	GET192F	GET195F
l ype	vertical, four-stroke, direct injection, air- cooled		vertical, four-stroke,	Single cylinder, vertical, four-stroke, direct injection, air- cooled
	88.75*90mm	75*77mm	92*75mm	95*75mm
Displacem ent	l	19:01cc	19:01cc	19:01cc
Compressi on Ratio	6.7/3000	7.8/3000	6.5/3000	8.1/3000
Rated Power (KWipm)	7.2/3600	7.3/3600	8.2/3600	8.7/3600
Rated Power (HPIIPm)	9.8/3600	10.3/3600	112/3600	11.8/3600
Rated Speed (rpm)		3000/3600		
Lowest rotation speed at zero loed		1300		
Lubricatin g system		Pressure splashad	Pressure splashad	Pressure splashad

These features provide a general overview of single-cylinder air-cooled diesel engines. However, it's important to note that specific engine models may have additional features or variations based on the manufacturer and intended application. Consulting the manufacturer's documentation or specifications for a particular engine model will provide more detailed and accurate information.



BZ7ge		#\$1. E.E. BE, BR. Rhibertings operas, vehicli for shore, deal reador, ar-cone				
US/46 bondote	me	ren	rente.	80.12		
HB Dipsoner	16.	(41)	296	10		
Edit Corposión Fast-		2001	0041	1901		
MESSE Tubel Frame	moon	9.5/9000 9.8/9800	3.800000 4.0001	5.7360 6.3360		
MERICA Subst Prosp	High	4,97000 1,27000	1.0000 1.4000	1.0300 8.0300		
MERCH Sales Speed	gen	3000 7 3600				
B-0.04 State special , was land	1000	- 100				
MRNX subnating system		EXTER Proper system				
Billioth Stating system		ROBSY 60 R Feori Statistical States				
Michiel ((EPRON) Relation desclorables to the sulput solid		BITT ATGODALE				
BART Factors		CH \$3.1 - RH 6.5.1 - RH 6.5.1 - RH 6.5.0 + number - 10.6 Current - 20.6 (striken) densit				
BARRY Tool link capacity	L.	2.0	3.0	8.6		
MARKENIERS For conjugacy selectronic geotopic trons		290-27000E 290-37000E	676.1000 00.87000	(75.1000 (81.51000		
REMARK Life of top		(O gaste or Self 1974-91, 1984-91				
発育物理量 Lube of repecty	1	1.75		1.00		
GB/GERM Starting mater reportly	11, 100	SVG6W				
5424018 Danjing pression requelly	V. 8	129 83A				
SURSE fallery squarity	V. m	501 20th	SIV 204s	12V 30An		
MERT Consideration (LRH.)	met	6001001168	400-400010	307407943		
PE to want	No.		20	- 4		











NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA