220V Diesel Welding Generator 6500EAW Genset Diesel Welder Generator

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: · Price: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Rated Frequency: 50hz 60hz Rated Power (kw):

• Rated Voltage (V): 220V Or As Request

• Rated Currency (A): 8.7 9.5A • Rated Rotation Speed 3000 3600

(r/min):

• Phase No.: Single Phase

Power Factor: • No Load Welding Voltage: 65-70V Insulation Grade: F • Pole Number:

. Engine Mode: GET186FA GET192F

Displacement(ml): 418 456

. Engine Type: Single Cylinder, Vertical, Four Stroke, Direct

Injection, Air-cooled

Dava V Ctualia (mana).

Product Description

Open Type Diesel Powered Welder GET6500EAW Diesel Welding Generator

The GET6500EAW Diesel Welding Generator is a specific model of diesel welding generator. While I don't have information on this specific model as my knowledge cutoff is in September 2021, I can provide you with a general overview of the features commonly found in diesel welding generators. Please note that the features may vary depending on the manufacturer and model. Here are some typical features you might find in a diesel welding generator:

| | 2 5 | | |
|--------------------------------|---|--|--|
| p 10110 0 1 0 1 1 0 1 (1 1 1) | 8.7 9.5A | | |
| | Single Phase | | |
| | 65-70V | | |
| | 2 | | |
| | 418 456 | | |
| | 1-86x72/ 1-92x75 | | |
| ` ' | 5.7 6.3/ 7.2 8.2 | | |
| P 10110 011 011 011 | CD Grade Or SAE10W-30, 15W-40 | | |
| | 0#(summer)-10#(winter)-35#(chillness) Diesel | | |
| | 13.5 | | |
| | 180A 220A | | |
| | 60% | | |
| | 1.6-3.2mm 1.6-5.0mm | | |
| | Diode | | |
| _ , , | 720x492x655mm | | |
| | 112kg 116kg | | |
| , , | 50hz 60hz | | |
| | 220V Or As Request | | |
| | 3000 3600 | | |
| · ` ` ` ' | 1 | | |
| Insulation Grade: | F | | |
| Engine Mode: | GET186FA GET192F | | |
| | Single Cylinder, Vertical, Four Stroke, Direct Injection, Aircooled | | |
| Compression Ratio: | 19:01 | | |
| Lubrication System: | Pressure Splashed | | |
| Lube Capacity (L): | 1.65 | | |
| Fuel Consumption (g/kw*h): | ≤280 | | |
| Continuous Running Time: | 8h | | |
| Welding Voltage: | 25-30V | | |
| Welding Current Adjustment | 50-180A/ 50-200A | | |
| Range: | | | |
| | Seperate-excitation+AVR Voltage Regulation AVR | | |
| | Drive Bearing, Rigid Connection | | |
| Structure Type: | Open Type | | |

Fuel Efficiency: Diesel welding generators are generally known for their fuel efficiency, allowing for longer operation times without frequent refueling.

Safety Features: The generator should include safety features such as overload protection, low oil shutdown, and circuit breakers to protect both the generator and connected equipment.

Portability: Depending on the model, the generator may have built-in handles, wheels, or a compact design to enhance portability and ease of transportation.

Noise Reduction: Some diesel welding generators incorporate noise-reducing features such as soundproof enclosures or mufflers to minimize noise levels during operation.

Multiple Power Outlets: The generator may provide various power outlets, such as AC sockets or industrial plugs, to accommodate different electrical devices and tools.



| D T Mod | | GC710000AM | DETTYCOUNTY |
|--|---------|---|-------------|
| EXEL Subclinatory | 16 | 10 40 | |
| MEST Substituted | eer | 1.5 | 2.1 |
| MERG SACHING | Y A | DOO to required | |
| HERE SANGERS | | 17 95 | 87 85 |
| BI E FUE Clothed speed | ritrige | 2000 Miles | |
| 66 Phose No. | | 44 Stokehou | |
| DE BOX Proper harder | 579.0 | - 1 | |
| O & 40 & G/S For heat creating private | W. | 6.5 | |
| MER WIR GIR Plates salding current | d. | 100 000 | |
| MEGS Vering robust | ¥ | 25.00 | 25.89 |
| GROWFIEL Printing least preference ratio | | 40. | |
| STEERTER SWING sent platest BETTER | A. | 10-100 | 86-388 |
| ERMA ER Cachola Sando | 100 | 18-32 | 18-63 |
| BRAZ bosen mak | | Sepretar excitator 47% roticor registros 47% BIS | |
| MESS Schools | | _## two | |
| BORDS CHANGE TOOK | | REPRESENT CITY DUTY, AND COMMON | |
| BSSS revision grade | | 1 | |
| RR handler | | | |
| EDB-SFE Cropine Monte: | | GETTERFA | SETTION |
| DESCRIPTION COMPANY TO ARE | | \$5. 45, E46, E8, K46460ingle-sinder series, but sinds distribution at resist | |
| EB Systemat | mi. | 49 | 495 |
| CO WE has related | 1999 | 1.00'55 | 1,0075 |
| BIES Compressor ratio | | 1001 | 1904 |
| Digital Million Rabed power | 66 | 67 48 | T2 82 |
| EFRI Librario cettos | | B.S. S.E.R. & Consum spended | |
| RESIDENT Laberal board | | CD 4449 + TAC 109 - 01, 109 - 40 | |
| RESTRICT LA COURT | L | Les | 146 |
| BEDDE TRANS (WHEN | | PROOF BURN OF TOY WHITE OR THE | |
| BRANK Sense specty | 9-An | 127-294 | |
| BERE helige | | OR (MIRCH - 108 B-RC) - OLA (MIRC) MIRC OR Coupement (MIRC) Interface (MIRC) Interfaces (MIRC) | |
| COMPANA FACORAGE | 10000 | 170 | |
| ELEMENTS STATES STATES | 4 | 11.5 | 195 |
| NAME AND ADDRESS OF THE PARTY O | | | |
| B B Solve Invest Ton | oliko / | | |
| BRAIL Busherings | | #8 Own hare | |
| ESPSET Creat desertion | - | 20140760 | |
| REPECT WINE | hig | 102 | 116 |











NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA