

8500T Silent Diesel Generator Genset Diesel Silent 3000 Watt

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: · Price: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Rated Frequency: 50hz 60hz

Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3 • Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7

220V Or As Request • Rated Voltage (V):

• Rated Currency (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/

27.2 28.6

Rated Rotation Speed

(r/min):

3000 3600

• Phase No.: Single Phase

Power Factor: 1 F Insulation Grade: • Pole Number: 2

Self-excitation & Constant Voltage (AVR) Excitation Mode:

Panel Type: General Panel . Receptacle: Two Receptacles

Cammantian Dala

Product Description

GET8500T Silent Diesel Generator Single Phase Dual Fuel Quiet Generator

Quiet diesel generators come with various features and technologies that contribute to their reduced noise emissions. While the specific features may vary depending on the manufacturer and model, here are some common features found in quiet diesel generators:

B	Teal and
Rated Frequency:	50hz 60hz
Max Output (kw):	2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7
Rated Currency (A):	11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6
Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	164 150 150 153 161
Noise Level (7m):	72 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	296 418 456 498 531
Compression Ratio:	20:01, 19:01
Starting System:	Electric Start
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 30Ah
Fuel Tank Capacity (L):	15
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	945*555*700
Working Assorting Weight (kg):	179 185 186 186 187
Structure Type:	Silent Type
Cylinder Nobore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
,	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-
Rated Power:	8.7/3600
Lubrication System:	Pressure Splashed
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	1.1/ 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280
	·

Soundproof Enclosure: Quiet diesel generators are typically equipped with a soundproof enclosure or housing made of materials designed to absorb and dampen noise. The enclosure helps to contain the sound and prevent it from escaping, reducing noise levels significantly.

Low Vibration Design: Quiet diesel generators often incorporate design elements to minimize vibrations, which can contribute to noise. This may include the use of vibration-dampening mounts, rubber isolators, or anti-vibration pads to reduce mechanical vibrations and noise transmission.

Advanced Exhaust System: A quiet diesel generator will have an exhaust system designed to minimize noise. This can include the use of high-quality mufflers, resonators, and insulated exhaust pipes to dampen the noise generated during the combustion process.

Engine Design and Insulation: The engine of a quiet diesel generator may feature advanced design and insulation to reduce noise emissions. This can include optimized combustion processes, improved engine insulation materials, and reduced mechanical friction to minimize noise.

Efficient Cooling System: Quiet diesel generators incorporate efficient cooling systems that operate with minimal noise. This may include the use of silent fans, insulated coolant lines, and carefully designed airflow paths to reduce noise associated with cooling.

Smart Load and Speed Control: Some quiet diesel generators come with smart load and speed control features. These systems automatically adjust the engine speed and power output based on the load demand, optimizing fuel consumption and reducing noise levels during low-demand periods.



			CATTROOP			
BERE Osterbanery Dr.)	0013000	100.700001	D 4	0019000	100,1900001	
BERN Debrinded (MV)	28 28	65.48	48 53	17.40	60 63	
BARR No. name (NV)	37.30	10.10	12 13	63.69	68.32	
BEE D.N. Platest vollage (5)	200/0000X PER 200/or as respect					
BERE Paletonerry (4)	TIS TET 204 218 218 207 208 272 272 208					
EXPRIS Finish Address speed Colone 1	112 127	200 213	3000 3000	207.212	22.00	
BIE Class MC	## troughter					
SHEET Francis Solley (Cos. ©)	-					
BORRE SOLUTION TOWN						
SIS THE CUITED						
Big of Cycleton male	A BREET I WANTED SAFE ANTHORNE WHOSE STOPE					
EMERIC Front Type	# # # # Formal Part					
RITER DOUBLE	AT BERN BE To make in					
Bit 685 Consetor pris	A Billion					
BROC NY OCHY MAN	MARINE Connection code actual					
#HER-H Owest direction LL (VIPAH) (mm.)	647-557-704	8650076	945 555 700	640'000'004	86.9879	
B/E Dor serials (to)	100	-69	150	100	- 10	
SPACE BE Station assessing unipe by	(3)	185	186	100	167	
CONTROL SOLD Superioral (No.)	- 10	- 5	- 10	- 10	19	
BRIDE Stratus has	Station					
EXPERT CONTRACTOR	DETTOR	OFTSBIFA	CETIME	DETINE	CHETTANE	
EDRIED Drune Type	WE, T.E. Big., Sell, Alleader traps ration, vertice four-dries, description, or-coost					
Night (city 48 page 10 consumo (con)	1-996 1-975 1-975 1-975					
BIRE Displacement Int	796	6.0	400	499	500	
Militer Route many front power	3.55/2006 41800	5.70000-6.93000	5-5-9000 F (19900)	1 6 950 5 2 7600	8.1/0000/d.7/08/	
END COMMUNICATION	PROFIT	1961	975	1994	1991	
BLR C.S. Lubricolor system	E to NAME of Property solution					
Exiting Severy system	600 liete ser					
MIRRIE CAN NO.	OR (EX) - NR (SX) - MR (SE) SE desir(4 surrey) - NR (sintr) - NR Intines desir					
NAME OF THE PARTY	CD page or SME SM. 30, 1507-40					
PERSONAL Later companies (L.)		1.65	145	1.46	1.66	
Bild field \$100 Starting motor capacity (19-68)	121 3369	107 0 000	SEY E-MAR	129 1269	127 1,269	
ESESERS Charging personal respectly (V-A)	GW 8.36	129 8.36	GV AM	GW 8.34	120 836	
製化的機器 Bulley (aposity (マイト)	TOP SOME TOY SAME					
MESSES Functionarytim (glar's)	+260	+280	<380	+290	<280	
教養教育者 Fuerteen Inpecty (1.1)	. 10	19	10	70	19	
PARTECON CONTINUE COVERN THE LTD	71					

GET Wuxi Guangertai Power Machinery Co.,Ltd

13813650506

2415819289@qq.com

@ dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA