



0.9KW 1.2KW Ultra Silent Generator Ultra Quiet Dual Fuel Generator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
- Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- Insulation Grade: F
- Pole Number: 2
- Excitation Mode: Self-excitation & Constant Voltage (AVR)
- Panel Type: General Panel
- Receptacle: Two Receptacles
- Operation Mode: Without

for more products please visit us on diesenginepumps.com

Product Description

GET7500T Ultra Quiet Rv Generator White Red Black

Ultra-silent diesel generators, with their exceptionally low noise levels, find applications in various settings where noise reduction is critical. Here are some specific applications where ultra-silent diesel generators are commonly used:

Outdoor Recreation: Ultra-silent diesel generators are suitable for outdoor recreational activities where a quiet environment is desired. They are used in campgrounds, national parks, and RV parks to provide power for camping trailers, recreational vehicles, and amenities while minimizing noise disturbances to fellow campers.

Residential Construction Sites: Construction sites in residential areas often face noise restrictions, and ultra-silent diesel generators are employed to power tools, machinery, and temporary lighting without causing significant noise disturbances to nearby residents.

Telecommunication and Data Centers: Ultra-silent diesel generators are crucial in telecommunication facilities and data centers where uninterrupted power supply is essential for uninterrupted operations. These generators provide backup power while minimizing noise interference that could affect sensitive equipment and communication systems.

Remote Locations and Off-Grid Power: In remote areas and off-grid locations, ultra-silent diesel generators serve as a reliable power source without disturbing the tranquility of the surroundings. They are used in remote research stations, mining operations, and off-grid residences where silence is valued.

Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	164 150 150 153 161
Noise Level (7m):	72 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	296 418 456 498 531
Compression Ratio:	20:01, 19:01
Starting System:	Electric Start
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 30Ah
Fuel Tank Capacity (L):	15
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	945*555*700
Working Assorting Weight (kg):	179 185 186 186 187
Structure Type:	Silent Type
Cylinder No. -bore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	1.1/ 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280
Continuous Running Time:	11h 8h 8h 7h 7h



参数表 Specifications

Model	GET7500T	GET7500T	GET7500T	GET7500T	GET7500T
额定功率 (kW)	2.5	2.8	4.5	4.8	5.0
额定电压 (V)	220	220	220	220	220
额定频率 (Hz)	50	50	50	50	50
额定转速 (r/min)	3000	3000	3000	3000	3000
额定电流 (A)	11.4	12.7	20.5	21.8	22.9
额定功率因数	1.0	1.0	1.0	1.0	1.0
额定效率 (%)	85	85	85	85	85
额定油耗 (g/kWh)	≤280	≤280	≤280	≤280	≤280
额定运行时间 (h)	11	8	8	7	7
额定重量 (kg)	164	150	150	153	161
额定噪音 (dB)	72	72	72	72	72
额定尺寸 (mm)	945*555*700	945*555*700	945*555*700	945*555*700	945*555*700
额定功率 (kW)	2.5	2.8	4.5	4.8	5.0
额定电压 (V)	220	220	220	220	220
额定频率 (Hz)	50	50	50	50	50
额定转速 (r/min)	3000	3000	3000	3000	3000
额定电流 (A)	11.4	12.7	20.5	21.8	22.9
额定功率因数	1.0	1.0	1.0	1.0	1.0
额定效率 (%)	85	85	85	85	85
额定油耗 (g/kWh)	≤280	≤280	≤280	≤280	≤280
额定运行时间 (h)	11	8	8	7	7
额定重量 (kg)	164	150	150	153	161
额定噪音 (dB)	72	72	72	72	72
额定尺寸 (mm)	945*555*700	945*555*700	945*555*700	945*555*700	945*555*700



Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA