Electric Start 7500T Ultra Quiet Diesel Generator Single Phase 220V

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Rated Frequency: 50hz 60hz

Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3 • Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7

220V Or As Request • Rated Voltage (V):

• Rated Currency (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/

27.2 28.6

Rated Rotation Speed

(r/min):

3000 3600

• Phase No.: Single Phase

Power Factor: F Insulation Grade: • Pole Number: 2

Excitation Mode: Self-excitation & Constant Voltage (AVR)

Panel Type: General Panel . Receptacle: Two Receptacles

Cammantian Dala 1 A /: 4 la a . . . 4

Product Description

GET7500T Ultra Quiet Dual Fuel Generator Ultra Quiet RV Generator

Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	164 150 150 153 161
Noise Level (7m):	72 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	296 418 456 498 531
Compression Ratio:	20:01, 19:01
Starting System:	Electric Start
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 30Ah
Fuel Tank Capacity (L):	15
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	945*555*700
Working Assorting Weight (kg):	179 185 186 186 187
Structure Type:	Silent Type
Cylinder Nobore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000- 8.7/3600
Lubrication System:	Pressure Splashed
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	1.1/ 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280
Continuous Running Time:	11h 8h 8h 7h 7h

The working principle of an ultra-quiet diesel generator is based on the fundamental principles of a diesel engine and electrical generator. Here are the key steps involved in the operation of an ultra-quiet diesel generator:

Combustion Process: The process begins with the combustion of diesel fuel inside the diesel engine. The fuel is injected into the combustion chamber, and it mixes with compressed air. This mixture is ignited by the heat generated from the compression of the air, leading to the rapid expansion of gases.

Mechanical Energy Generation: The combustion process creates a high-pressure and high-temperature gas mixture. As the gases expand, they create a force that pushes the piston downward in the engine cylinder. The reciprocating motion of the piston is converted into rotational motion through a connecting rod and crankshaft.

Crankshaft Rotation: The rotation of the crankshaft converts the linear motion of the pistons into a continuous circular motion. The crankshaft is connected to the generator's rotor, which is equipped with a set of windings.

Electromagnetic Induction: The rotor windings interact with a set of stationary windings, known as the stator windings, surrounding them. As the rotor rotates, it generates a changing magnetic field. This changing magnetic field induces an electric current in the stator windings through the process of electromagnetic induction.

Electricity Generation: The induced electric current in the stator windings produces alternating current (AC) electricity. This AC electricity is the primary output of the generator and can be used to power electrical devices and appliances.

Voltage Regulation: Ultra-quiet diesel generators often include a voltage regulator to maintain a stable and consistent voltage output. The voltage regulator adjusts the excitation current supplied to the rotor windings, regulating the magnetic field strength and ensuring a constant voltage output.

Noise Reduction Mechanisms: Ultra-quiet diesel generators incorporate various noise reduction mechanisms to minimize noise emissions. These mechanisms include soundproof enclosures, acoustic insulation, specialized exhaust systems, and low-vibration designs. These features work together to reduce noise transmission and dampen the sound generated during the combustion and mechanical processes.

Cooling System: Ultra-quiet diesel generators have cooling systems to regulate the temperature of the engine and ensure efficient operation. The cooling system typically consists of a radiator, coolant fluid, and a circulation pump that dissipates heat generated during the combustion process.



PR Inch	MITMANE	OCTIMANT	CETTONE	BITTANKE	OCTOBORT.	
BERS /backtonery Nr.		30.130001	D 44	00.000		
BERN Debrinded (MV)	28.28	65.43	48 53	17.40	60 63	
BARR No. man (NY)	37 30	60.03	13 14	63.69	48.33	
BEE BOX Plaint voltage (5)	SECURITIES AND TOO AN ARROW.					
BERGE Paled coverage (4.)	713 127	204 718	21.8 20.7	20.0 27.2	272 28.6	
BESTRIE Photochystation speed Culture 1	200 300					
BIR Class IC	RETYGLING					
SHEET FORM SHEET COL ® 7						
BIRRY HARRY DIACE						
BIR The number						
BREST Symbol mile	A SMEX 1 Stands I Sub-particular variables and stands					
EMERIC From Non	WHITE Ground Panel					
BIT ES Chouses	N 1 6 6 8 6 7 to contain					
BOARD Consents rate	8 Releas					
Ballot, sty (60 sty output	MARINE Connection such asked					
#HER-H Owest direction LL (VIPAH) (mm.)	647-657-704	86500768	945 956 700	640'000'004	86.9879	
BE Do worth I to I	164	-69	150	+63	- 40	
grow King Spinors asserted unique (to)	(3)	185	156	100	167	
BBBBI ICAL Schedule 7m	- 9	79	10	79	79	
BRIDE Stratus has	Service					
EXPERT CONVENIENCE	DETTOR	OFTSBIFA	CETTURE	DETINE	CHETTANE	
EDRIED Drune Ture	#8, 25, 89, 36, Read tops upon vetos top-data decirpator, or-cont					
Night (city 48 page 10 consumo (con)	1-1990	1-9575	1.075	1-979	1-9775	
BIRE Displacement Int	794	6.0	450	499	500	
Bill to Book mad front year	3.88/2006 418000	5 200000 6 9 20000	8-5-9000 F 2/2000	16/3000 5 2/3600	8.1/2000/d.7/28/	
ENE Companion ratio	PROFIT	1001	78.00	1998	1961	
BLR CH Lubricator system	E to NAME of Pressure soluted					
Expensi Causes sustain	#GD Date and					
MARIE For you	04 (EX)-104 (SX)-364 (GR) SS deal(4 (some)-54 (sinte)-364 (sinter) deal					
ACRES S Later of Street	Channel of Maria M. 100 At					
ESTATE Literappin (L.)	- 14	1.66	145	1.85	1.66	
SIGNATED States make squarts (P. 48)	124 5369	127 09/8	SN EMM	120 1,200	127 1,269	
ESESSES Charges personal reports V-A	50V 8.36	129 836	SIV AM	50Y 8.36	129 8.56	
BRANK Schreigenbrig-At-1	107 MAG 170 MAG					
MERRE functionable (state)	+260	+280	<386	+299	<380	
MERRE TWEEN INCOME ILI	- 11	19	13	70	19	
BYESFERR CORNING OWING SING N	- 11					

GET Wuxi Guangertai Power Machinery Co.,Ltd

13813650506

2415819289@qq.com



e dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA