



## 8m 6m Industrial Diesel Water Pump For Agriculture Low Noise

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Model Number: GETDP150
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



### Product Specification

- Type: Diesel Clean Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m<sup>3</sup>/h: 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm<sup>3</sup>): 247 290 410 490

for more products please visit us on [diesenginepumps.com](http://diesenginepumps.com)

## Product Description

### Electric Diesel Engine Pumps Diesel Engine Water Pump

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	

Electric diesel engine pumps, also known as electric-driven diesel pumps, are versatile pumping systems that combine the power of a diesel engine with the convenience and efficiency of an electric motor. These pumps find application in various industries and sectors. Some common applications of electric diesel engine pumps include:

**Utilities and Power Generation:** Electric diesel engine pumps are used in utilities and power generation facilities for water intake, cooling systems, and emergency backup applications. They assist in maintaining proper water circulation and cooling in power plants, ensuring efficient operations and preventing equipment damage.

**Environmental Remediation:** Electric diesel engine pumps are employed in environmental remediation projects to pump and transfer contaminated water, slurry, or other fluids during cleanup and remediation processes.



参数表 Specifications

参数名称	2000W	3000W	4000W	5000W	6000W
额定流量 (Rated Flow)	48 T/h	54 T/h	60 T/h	66 T/h	72 T/h
最大流量 (Max. Flow)	48 T/h	54 T/h	60 T/h	66 T/h	72 T/h
最大扬程 (Max. Lift)	60 m	80 m	100 m	120 m	150 m
额定转速 (Rated Speed)	3600 rpm	3600 rpm	3600 rpm	3600 rpm	3600 rpm
发动机型号 (Engine Model)	190F	192	195	198	200
净重 (Net Weight)	91 kg	94 kg	100 kg	105 kg	110 kg
总重 (Gross Weight)	100 kg	103 kg	110 kg	115 kg	120 kg
尺寸 (Dimensions)	450x350x450 mm	450x350x450 mm	450x350x450 mm	450x350x450 mm	450x350x450 mm
油箱容量 (Fuel Capacity)	20 L	20 L	20 L	20 L	20 L
启动系统 (Starting System)	手动启动 (Manual)	手动启动 (Manual)	手动启动 (Manual)	手动启动 (Manual)	手动启动 (Manual)
其他特性 (Other Features)	自吸式 (Self-priming)	自吸式 (Self-priming)	自吸式 (Self-priming)	自吸式 (Self-priming)	自吸式 (Self-priming)