



Red Heavy Duty Diesel Water Pump 3 Inch Water Pump Diesel

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Model Number: GETDP150
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Diesel Engine Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h: 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m: 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 290 410 490

for more products please visit us on dieselenginepumps.com

Product Description

Industrial Diesel Engine Pumps Red Diesel Engine Water Pump

Industrial diesel engine pumps are widely used in various applications, including irrigation, construction, mining, oil and gas, and wastewater management. These pumps are designed to provide high-performance pumping capabilities in demanding industrial environments. Here are some key features and characteristics of industrial diesel engine pumps:

Diesel Engine Power: Industrial diesel engine pumps are equipped with powerful diesel engines that provide the necessary torque and horsepower to drive the pump system efficiently. Diesel engines are known for their robustness, durability, and ability to handle heavy-duty operations.

High Flow Rates: Industrial diesel engine pumps are designed to handle large volumes of fluid. They can deliver high flow rates, allowing for efficient transfer or movement of liquids over long distances or at significant elevations.

High Pressure Capability: In addition to high flow rates, industrial diesel engine pumps can generate substantial pressure to overcome resistance in the system. This makes them suitable for applications that require pumping liquids against high head pressures or through long pipelines.

Durable Construction: Industrial diesel engine pumps are typically constructed with durable materials such as cast iron, stainless steel, or other corrosion-resistant alloys. This ensures their ability to withstand harsh operating conditions, including exposure to abrasive fluids or corrosive environments.

Mobility and Portability: Many industrial diesel engine pumps are designed to be mobile or portable, allowing for easy transportation and flexibility in different job sites. They may have built-in handles, wheels, or trailers for convenient movement. Industrial diesel engine pumps play a critical role in various industrial applications, providing reliable and efficient pumping solutions. Their powerful diesel engines, high flow rates, and durability make them well-suited for demanding environments where reliable fluid transfer is essential.

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	



参数表 Specifications

Model 型号	10T/1000	15T/1500	20T/2000	25T/2500
水泵类型 Type	Clean water pump	Clean water pump	Clean water pump	Clean water pump
进出口口径 Inlet/Outlet Port Diameter	mm 25	50/75	80/100	100/125
最大流量 Discharge capacity	m³/h	30	40	110
最大扬程 Max Head	m	30	30	30
自吸时间 Self-priming Time	min	10	10	10
额定转速 Rated speed	rpm	3600	3600	3600
净重 Net weight	kg	91	91	91
外形尺寸 Overall Dimensions	mm	510*450*540	580*500*580	650*550*580
净重 Net weight	kg	44	50	71
额定功率 Rated Power	kw	2.9	4	5.5
燃油消耗率 Fuel consumption	g/kwh	200	200	200
噪音 Noise	dB	247	247	247
发动机 Engine	190F	190F	190F	190F
冷却系统 Cooling system	Water-cooled	Water-cooled	Water-cooled	Water-cooled
最大流量 Discharge capacity	m³/h	30	40	110
最大扬程 Max Head	m	30	30	30



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA